

HIGH PRESSURE FIRE HOSE REEL

Pamet presents High Pressure Fire Hose Reel. Our product is available in different drum width (depending on required hose length and diameter: 20, 40, 60, 90 and 120m) making it a universal device fittable to all fire and rescue trucks.

TECHNICAL SPECIFICATIONS:

Hose length: 40, 60, 90, 120 m

Hose ID: 19 mm

Working pressure: 40 atm = 4 MPa

Test pressure: 80 atm = 8 MPa

Inlet coupling: on right or left side: G1"

Hose guide: roller guide, retractable, on top or bottom of the drum

Rewind: A) electric 24 or 12V plus manual (crank); B) only manual

Break: manual with dial

Dims (version with 60 m hose): D 533 mm x H 555 mm x W 672 mm

Weight (electric w/o hose): 36 kg

Designed & produced in Poland.

Made of durable quality materials, rust-protected (parts exposed to permanent water contact made of stainless steel).



Special inserts assure correct hose alignment, which in turn allows extremely stable and unrestricted water (or foam) supply at 40 atm, regardless of how much hose has been unwound.

Electronic control box is overload-protected and waterproof.



Pump inlet.

Electrical rewind can be switched to manual rewind (crank driven). System fitted with a safety break.



Retractable roller guide, can be fitted on top or bottom.



Control foot switch.